



RZ0165WRB

Wall Recessed Light With Die-casting Aluminum Led 1W 85lm CRI80 D50mm 50.000h IP65

RZ0365WRB

Wall Recessed Light With Die-casting Aluminum Led 3W 255lm CRI80 D50mm 50.000h IP65

Description

Recessed luminaire that can be installed in concrete floors or wall. It is designed to use white monochrome LED lamps, for lighting, fixed optic.

Housing: Die-casting Aluminum, Surface optimised for reduced accumulation of dirt, with a high level of weather resistance, Durable silicone rubber gasket.

Luminaire head with transparent toughened non-reflective glass, resist the impact and friction.

Control gear: Longitudinally watertight cable, 1 cable entries. 2 or 3-pole terminal block.

Installation with separate connection sleeve.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP65: dust-proof and water jet-proof.



Technical data

Light source	LED COB	
System Wattage	1W	3W
Luminous flux	85lm	255lm
Number of led lamp	-	
Luminous efficiency	85lm/w or option	
Colour Temperature	2700K, 3000K, 4000K, 6000K	
Colour Rendering Index	CRI>80, [CRI>90]	
Colour Deviation	SDCM<3	
Beam Angle	Diffused	
Rotation Angle	-	
Anti-glare Rating	-	
Service Lifetime	50.000 Hrs L80 B20 Ta35	
Ingress Protection	IP65	
Operation Voltage	220VAC	24VDC
Operation Temperature	-30°C ~ 50°C	
Frame	Aluminum	
Finishing	Matt Black, Matt White	
Lighting control (option)	Dali, 0-10V, Triac, Wireless	

Accessories

-

Notes

-