

### RZ0344WRA

Wall Recessed Light Led 3W 210lm 88\*88\*H48mm 50.000h IP44 With Recessed box



#### Description

Housing: Die-casting Aluminum, Pre-treated before powder coating ensuring high corrosion resistance, No-Rinse surface treatment. Optimised surface for reduced accumulation of dirt, with a high level of weather resistance. Durable silicone rubber gasket.


Recessed housing: PVC. Clamp extension: spring kit.


Control gear: 2 cable entries. Through-wiring possible. 3-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Built-in driver for AC-input.

Dimming driver can be optionally sold separately [option AC in-put]: Dali, 0-10V, Wireless.



 78\*78\*48mm



#### Technical data

Light source	LED COB
System Wattage	3W
Luminous flux	210lm
Number of led lamp	-
Luminous efficiency	70lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>80, [CRI>90]
Colour Deviation	SDCM<3
Beam Angle	Diffused
Rotation Angle	-
Anti-glare Rating	-
Service Lifetime	50.000 Hrs L80 B20 Ta35
Ingress Protection	IP44
Operation Voltage	220-240VAC, 50Hz   24VDC
Operation Temperature	-30°C ~ 50°C
Frame	Aluminum
Finishing	Matt White, Matt Black or Option
Lighting control (option)	Dali, 0-10V, Triac, Wireless

More option: Sensor



#### Accessories

Wall recessed box

#### Notes

-