



.3W



.6W



.10W

RZ0365SMS

Surface Mounted Step Light With Die-casting Aluminum Led 3W 210lm CRI80 Diffused 220VAC 30*60*L130mm 50.000h IP65

RZ0665SMS

Surface Mounted Step Light With Die-casting Aluminum Led 6W 420lm CRI80 Diffused 220VAC 35*63*L170mm 50.000h IP65

RZ1065SMS

Surface Mounted Step Light With Die-casting Aluminum Led 10W 700lm CRI80 Diffused 220VAC 46*81*L240mm 50.000h IP65

Description

Housing: Die-casting Aluminum, Pre-treated before powder coating ensuring high corrosion resistance, No-Rinse surface treatment. Optimised surface for reduced accumulation of dirt, with a high level of weather resistance. Durable silicone rubber gasket.

Recessed housing: PVC

Control gear: 1 cable entries. 3-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP65: dust-proof and water jet-proof.



Technical data

Light source	LED SMD		
System Wattage	3W	6W	10W
Luminous flux	210lm	420lm	700lm
Number of led lamp	-		
Luminous efficiency	70lm/w or option		
Colour Temperature	2700K, 3000K, 4000K, 6000K		
Colour Rendering Index	CRI>80, [CRI>90]		
Colour Deviation	SDCM<3		
Beam Angle	Asymmetric		
Rotation Angle	-		
Anti-glare Rating	-		
Service Lifetime	50.000 Hrs L80 B20 Ta35		
Ingress Protection	IP65		
Operation Voltage	100-240VAC, 50Hz		
Operation Temperature	-30°C ~ 50°C		
Frame	Aluminum		
Finishing	Grey, Matt White, Matt Black or Option		
Lighting control (option)	Dali, 0-10V, Triac, Wireless		

Accessories

-

Notes

-

