

### RZ03PDB

Pendant Light With Aluminum and Steel Led 3W 150lm CRI90 30° 220VAC D40\*H500mm 50.000h IP20




.RZ03PDB

### RZ05PDC

Pendant Light With Steel and Acrylic Diffuser Led 5W 400lm CRI90 220VAC D40\*H500mm 50.000h IP20



.RZ05PDC



### Description

Designed can be surface mounted for the Decorative Lamp. With the modularized system, it's easy to use and easy to maintain.

Cylinder: aluminium profile, powder-coated.

Housing: Aluminium, with connection cable. Includes control gear with Led driver. 3-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Finish options: Matt White, Matt Black, Chrome, Satin Nickel, Brushed brass, Black bronze, Customized.

Protection Class I.



### Technical data

Light source	LED COB	
System Wattage	3W	5W
Luminous flux	150lm	400lm
Luminous efficiency	50lm/w or option	80lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K	
Colour Rendering Index	CRI>90	
Colour Deviation	SDCM<3	
Beam Angle	30°	Diffused
Rotation	-	
Tilt Angle	-	
Anti-glare Rating	UGR<19	
Service Lifetime	50.000 Hrs L70 B20 Ta25	
Ingress Protection	IP20	
Operation Voltage	220-240VAC, 50Hz	
Operation Temperature	-20°C ~ 45°C	
Frame	Aluminum	
Finishing	Matt White, Matt Black, Customized	
Installation	Surface mounted	
Switch	-	
Lighting control (option)	Dali, 0-10V, Triac, Wireless	

### Accessories

-

### Notes

-

