


### RZ0468SLS

Floodlight With Stainless Steel 316 Body, Anti-Corrosion, Transparent Toughened Glass Led 4W 320lm CRI80 24VDC D42 50.000h IP68



### Description

Outdoor floodlight designed to use LED lamps and a spot optic. Consists of an optical assembly and a base.

Housing, hinge and mounting plate: Stainless Steel 316 Body, Anti-Corrosion, ensures even in salty environments, especially suitable for underwater lighting. Optimised surface for reduced accumulation of dirt, with a high level of weather resistance. Hinge with 130° tilt. Mounting plate rotatable through 350°.


Luminaire head with transparent toughened non-reflective glass, resist the impact and friction.

Control gear: Longitudinally watertight cable, 1 cable entries. 2-pole terminal block.


LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP68: Protection against dust ingress, continuous immersion up to 3m deep.



### Technical data



Light source	LED COB
System Wattage	4W
Luminous flux	320lm
Number of led lamp	1 Led
Luminous efficiency	80lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>80, [CRI>90]
Colour Deviation	SDCM<3
Beam Angle	8°, 15°, 24°, 36°, 50°, [15x40°]
Rotation Angle	130° Tilt   350° Swivel
Anti-glare Rating	Accessory options
Service Lifetime	50.000 Hrs L80 B20 Ta35
Ingress Protection	IP68
Operation Voltage	24VDC
Operation Temperature	-30°C ~ 50°C
Frame	Stainless Steel 316
Finishing	Non-Color or Option
Lighting control (option)	Dali, 0-10V, Triac, Wireless

### Accessories

-

### Notes

-

