





### **RZ0767IGS**

Inground Light Stainless Steel 316 Cover, Anti-Corrosion, Transparent Toughened Glass Led 7W 490lm CRI80 24VDC 50.000h IP67 With Recessed Box



### RZ0567IGS


Inground Light Stainless Steel 316 Cover, Anti-Corrosion, Frosted Tempered Glass Led 5W 150lm CRI80 24VDC 50.000h IP67 With Recessed Box



More Option:







## Description

Recessed luminaire that can be installed in concrete floors or in the ground. It is designed to use LED lamps, for lighting, fixed optic.

Housing: Die-casting Aluminum with Stainless Steel 316 Cover, Anti-Corrosion, No-Rinse surface treatment. Surface with electrostatic plastic coating and Optimised for reduced accumulation of dirt, with a high level of weather resistance. Stainless steel fasteners in grade 316, Durable silicone rubber gasket.

Luminaire head with transparent toughened non-reflective glass, resist the impact and friction.

Control gear: Longitudinally watertight cable, 1 cable entries. [3] 2-pole terminal block. Installation with separate connection sleeve.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless. Protection mode IP67: dust-proof and and accidental immersion up to 1m deep.

Suitable for walk-over with a maximum static load resistance of 3000kg.



















# **Technical data**

Light source LED COB System Wattage 7W 5W Luminous flux 490lm 150lm

Number of led lamp 4 Led

Luminous efficiency 80lm/w or option

Colour Temperature 2700K, 3000K, 4000K, 6000K, [R.G.B]

Colour Rendering Index CRI>80 Colour Deviation SDCM<3

Beam Angle 8°, 12°, 22°, 36° Diffused

Rotation Angle Anti-glare Rating

Service Lifetime 50.000 Hrs L80 B20 Ta25

**Ingress Protection** IP67 Operation Voltage 24VDC **Operation Temperature** -30°C ~ 50°C

Frame Aluminum & Stainless Steel 316 Cover

Finishing Non-Color

Lighting control (option) Dali, 0-10V, Triac, Wireless, DMX512



## Accessories

# **Notes**