



Model	Dimension	Cut-out
RZ0580DLB	D100*H50mm	D80mm
RZ0795DLB	D118*H60mm	D95mm
RZ0995DLB	D118*H60mm	D95mm
RZ12125DLB	D145*H75mm	D125mm
RZ15150DLB	D170*H85mm	D150mm
RZ18160DLB	D190*H95mm	D160mm
RZ20160DLB	D190*H95mm	D160mm
RZ24200DLB	D230*H105mm	D200mm
RZ30200DLB	D230*H105mm	D200mm

RZ0580DLB

Recessed Downlight Led 5W 425lm CRI80 120° D100 50.000h White IP44

RZ0795DLB

Recessed Downlight Led 7W 595lm CRI80 120° D118 50.000h White IP44

RZ0995DLB

Recessed Downlight Led 9W 765lm CRI80 120° D118 50.000h White IP44

RZ12125DLB

Recessed Downlight Led 12W 1020lm CRI80 120° D145 50.000h White IP44

RZ15150DLB

Recessed Downlight Led 15W 1275lm CRI80 120° D170 50.000h White IP44

RZ18160DLB

Recessed Downlight Led 18W 1530lm CRI80 120° D190 50.000h White IP44

RZ20160DLB

Recessed Downlight Led 18W 1700lm CRI80 120° D190 50.000h White IP44

RZ24200DLB

Recessed Downlight Led 24W 2040lm CRI80 120° D230 50.000h White IP44

RZ30200DLB

Recessed Downlight Led 30W 2550lm CRI80 120° D230 50.000h White IP44

Description

Housing: cast aluminium, excellent thermal management can effectively guarantee the LED's long-term stability. The front panel board is high translucent acrylic, which ensures the light even, soft and high transmittance. Instant start, no flickering, no humming, no hazardous material.

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.



Technical data

Light source	LED SMD
System Wattage	5W 7W 9W 12W 15W 18W 20W 24W 30W
Luminous flux	425lm ~ 2550lm
Luminous efficiency	85lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>80
Colour Deviation	SDCM<3
Beam Angle	120°
Cut-Off Angle	-
Tilt Angle	-
Anti-glare Rating	UGR<19
Service Lifetime	50.000 Hrs L70 B30 Ta25
Ingress Protection	IP44
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum & PMMA
Finishing	Matt White
Lighting control (option)	Dali, 0-10V, Triac, Wireless

Accessories

-

Notes

-

