



### RZ0628MFR

Mini Fixed Downlight With Mirror Reflector Led 6W 480lm CRI90 D34 IP44



spot 12°			wide 38°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	2645	ø0.29	1	1269	ø0.59
2	661.2	ø0.58	2	317.2	ø1.19
3	293.9	ø0.87	3	141.0	ø1.79
4	165.9	ø1.16	4	79.31	ø2.38
5	105.8	ø1.45	5	50.76	ø2.98



#### Description

Housing: cast aluminium, designed as heat sink, with connection cable. Fixing ring: polymer, Baffle color: Dark Chrome, Chrome, Custom.

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 1-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: high-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Darklight reflector: Polymethyl, Chrome, Matt White, Customer. Anti-glare element: Polymethyl. Cut-off angle 40° with Anti-glare Rating UGR<16. Protection Class III.



#### Technical data

Light source	LED COB
System Wattage	6W - 150mA CC
Luminous flux	480lm
Luminous efficiency	80lm/w
Colour Temperature	2700K, 3000K, 4000K
Colour Rendering Index	CRI90
Colour Deviation	SDCM<3
Beam Angle	12°, 38°
Cut-Off Angle	40°
Tilt Angle	-
Anti-glare Rating	UGR<16
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP44
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum
Finishing	Matt White, Matt Black
Lighting control (option)	Dali, 0-10V, Triac, Wireless

#### Accessories

Interchangeable Reflector

#### Notes

