


RZ0628WSR

Mini Washer Downlight With Mirror Reflector Led 6W 480lm CRI90 60D D34 IP44



| wide 60° | | |
|----------|-------|-------|
| h(m) | E(lx) | ø(m) |
| 1 | 347.1 | ø0.95 |
| 2 | 86.90 | ø1.91 |
| 3 | 38.62 | ø2.87 |
| 4 | 21.73 | ø3.83 |
| 5 | 13.90 | ø4.79 |



Description

Housing: cast aluminium, designed as heat sink, with connection cable. Fixing ring: polymer, Baffle color: Dark Chrome, Chrome, Custom.

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 1-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: high-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Darklight reflector: Polymethyl, Chrome, Matt White, Customer. Anti-glare element: Polymethyl. Cut-off angle 30° with Anti-glare Rating UGR<19. Protection Class III.



Technical data

| | |
|---------------------------|------------------------------|
| Light source | LED COB |
| System Wattage | 6W - 150mA CC |
| Luminous flux | 480lm |
| Luminous efficiency | 80lm/w |
| Colour Temperature | 2700K, 3000K, 4000K |
| Colour Rendering Index | CRI90 |
| Colour Deviation | SDCM<3 |
| Beam Angle | 60° |
| Cut-Off Angle | 30° |
| Tilt Angle | - |
| Anti-glare Rating | UGR<19 |
| Service Lifetime | 50.000 Hrs L70 B20 Ta25 |
| Ingress Protection | IP54 |
| Operation Voltage | 220-240VAC, 50Hz |
| Operation Temperature | -20°C ~ 45°C |
| Frame | Aluminum |
| Finishing | Matt White, Matt Black |
| Lighting control (option) | Dali, 0-10V, Triac, Wireless |

Accessories

Interchangeable Reflector

Notes

