



# Indoor | Led Strip

### RZ0820CST

CCT Tunable Led Strip 8W/m 800lm [27K 380lm 60K 420lm] CRI90 2700K~6000K 24VDC 50.000h IP20 5M/roll




# RZ0865CST


CCT Tunable Led Strip 8W/m 800lm [27K 380lm 60K 420lm] CRI90 2700K~6000K 24VDC 50.000h IP65 5M/roll











## Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, 3M tape available. High-energy efficacy achieving up to 100lm/W, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area.

No need to attach aluminum profile for heat sink, various of connection accessories can be optionally sold separately.

Customized length available up to 5m per roll.

Change atmosphere by tuning the color temperature by Tunable White (2700K~6000K) and dimming control systems are for choice.

Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting

Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.





















## **Technical data**

Light source LED SMD System Wattage 8W/m

800lm Luminous flux [27K 380lm 60K 420lm]

Luminous efficiency 100lm/w or option

Colour Temperature 2700K ~ 6000K Adjustable

Colour Rendering Index CRI>90 [CRI95]

SDCM<3 Colour Deviation Beam Angle 120° Max.Length 5m Cut length 166.67mm

Led/m 60pcs

Anti-glare Rating 50.000 Hrs L70 B20 Ta25 Service Lifetime

**Ingress Protection** IP20 Option IP65

Operation Voltage 24VDC Operation Temperature -20°C ~ 45°C

Dali, 0-10V, Triac, Wireless, Tunable White Lighting control (option)

## **Accessories**









RZ-ST03A

RZ-ST03B RZ-ST0365A

RZ-ST0365B

#### Notes