



### RZ0820CST

CCT Tunable Led Strip 8W/m 800lm [27K 380lm 60K 420lm] CRI90 2700K~6000K 24VDC 50.000h IP20 5M/roll




### RZ0865CST

CCT Tunable Led Strip 8W/m 800lm [27K 380lm 60K 420lm] CRI90 2700K~6000K 24VDC 50.000h IP65 5M/roll



### Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, 3M tape available. High-energy efficacy achieving up to 100lm/W, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area. No need to attach aluminum profile for heat sink, various of connection accessories can be optionally sold separately. Customized length available up to 5m per roll. Change atmosphere by tuning the color temperature by Tunable White (2700K~6000K) and dimming control systems are for choice. Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting usages. Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.



### Technical data

Light source	LED SMD
System Wattage	8W/m
Luminous flux	800lm [27K 380lm 60K 420lm]
Luminous efficiency	100lm/w or option
Colour Temperature	2700K ~ 6000K Adjustable
Colour Rendering Index	CRI>90 [CRI95]
Colour Deviation	SDCM<3
Beam Angle	120°
Max.Length	5m
Cut length	166.67mm
Led/m	60pcs
Anti-glare Rating	-
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP20   IP65   Option
Operation Voltage	24VDC
Operation Temperature	-20°C ~ 45°C
Lighting control (option)	Dali, 0-10V, Triac, Wireless, Tunable White



### Accessories



### Notes

-