

RZ0775SDF

Square Recessed Adjustable Downlight With Anti-Glare Reflector Led 7W 595lm CRI90 50.000h IP44

RZ0975SDF




Square Recessed Adjustable Downlight With Anti-Glare Reflector Led 9W 765lm CRI90 50.000h IP44

RZ1275SDF

Square Recessed Adjustable Downlight With Anti-Glare Reflector Led 12W 1020lm CRI90 50.000h IP44

RZ1575SDF

Square Recessed Adjustable Downlight With Anti-Glare Reflector Led 15W 1275lm CRI90 50.000h IP44



Description

Housing: Cast aluminium, Adjustable, designed as heat sink, with connection cable. 0°-30° tilt, 355° rotation. Fixing ring: Matt White, Matt Black, Customized.
 Mounting ring: Expanding spring fixing for ceiling thicknesses of 5-30mm. Includes control gear with Led driver separate. 2-pole terminal block.
 LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.
 Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, DMX, Wireless, Tuya. Anti-glare cone with covered mounting detail: Mirror Silver, Mirror Black, Mirror Gold, Matt Silver, Matt Black, Matt Gold, Customized. High quality optical diffuser reduces LED dazzle light. Optical cut-off angle 45°. Deep anti-glare design, protect the eye.



Technical data

Light source	LED COB			
System Wattage	7W	9W	12W	15W
Luminous flux	595lm	765lm	1020lm	1275lm
Luminous efficiency	85lm/w or option			
Colour Temperature	2700K, 3000K, 4000K, 6000K, [2700~6500K]			
Colour Rendering Index	CRI>90; [CRI>95]			
Colour Deviation	SDCM<3			
Beam Angle	10°, 15°, 24°, 38°, 50°			
Cut-Off Angle	45°			
Rotation Angle	30° Tilt 355° Swivel			
Anti-glare Rating	UGR<16; [UGR<13]			
Service Lifetime	50.000 Hrs L80 B20 Ta25			
Ingress Protection	IP44			
Operation Voltage	220-240VAC, 50Hz			
Operation Temperature	-20°C ~ 45°C			
Frame	Aluminum			
Finishing	Matt White, Matt Black, Customized			
Reflector	Silver, Black, Gold, Customized			
Lighting control (option)	Dali, 0-10V, Triac, DMX, Wireless, Tuya App			

Accessories



Notes

-

