




.Type A




.Type B



.Type C



.Type D



.Type E

### RZ30UGE

Urban Garden Light With Die-Casting Aluminum Led 30W 3900lm CRI80 220VAC 10KV SPD 75.000h IP66 IK08

### RZ60UGE

Urban Garden Light With Die-Casting Aluminum Led 60W 7800lm CRI80 220VAC 10KV SPD 75.000h IP66 IK08

### RZ100UGE

Urban Garden Light With Die-Casting Aluminum Led 100W 13000lm CRI80 220VAC 10KV SPD 75.000h IP66 IK08

### Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.

Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.

Luminaire head with diffused light guidance ring.

Pole and Mounting accessories to be ordered separately.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: high-power LEDs on metal-core PCB. Surge protection 10kV.

Protection mode IP66: dust-proof and water jet-proof.

Maximum wind load resistance is 160km/h.



### Technical data

Light source	LED SMD		
System Wattage	30W	60W	100W
Luminous flux	3900lm	7800lm	13000lm
Number of led lamp	-		
Luminous efficiency	130lm/w or option		
Colour Temperature	3000K, 4000K, 5000K		
Colour Rendering Index	CRI>80		
Colour Deviation	SDCM<5		
Beam Angle	Diffused		
Rotation Angle	-		
Anti-glare Rating	-		
Service Lifetime	75.000 Hrs L70 B30 Ta35		
Ingress Protection	IP66		
Operation Voltage	100-264VAC, 50Hz		
Operation Temperature	-40°C ~ 60°C		
Frame	Aluminum		
Finishing	Grey, Matt Black or Option		
Lighting control (option)	Dali, 0-10V, Triac, Wireless		

### Accessories

-

### Notes

-