



Indoor | Led Strip

RZ1020ST

Led Strip 10W/m 1000lm CRI90 24VDC 50.000h IP20 5M/roll




RZ1065ST

Led Strip 10W/m 1000lm CRI90 24VDC 50.000h IP65 5M/roll








1.4mm



10.2mm







Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, 3M tape available. High-energy efficacy achieving up to 100lm/W, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area.

No need to attach aluminum profile for heat sink, various of connection accessories can be optionally sold separately.

Customized length available up to 5m per roll.

Change atmosphere by tuning the color temperature (2000K to 6000K) and dimming control systems are for choice.

Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting usages.

Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.



















Technical data

Light source LED SMD
System Wattage 10W/m
Luminous flux 1000lm
Luminous efficiency 100lm/w

uminous efficiency 100lm/w or option

Colour Temperature 2700K, 3000K, 4000K, 6000K

Colour Rendering Index CRI>90 [CRI95]

Colour Deviation SDCM<3
Beam Angle 120°
Max.Length 5m
Cut length 71.4mm
Led/m 98pcs
Anti-glare Rating -

Service Lifetime 50.000 Hrs L70 B20 Ta25

Ingress Protection IP20 | IP65 | Option

Operation Voltage 24VDC Operation Temperature -20°C ~ 45 °C

Lighting control (option) Dali, 0-10V, Triac, Wireless

Accessories









RZ-ST02A RZ-ST02B

RZ-ST0265A

RZ-ST0265B

Notes

_

RIZO | Lighting & Solution - 1 - https://rizo-light.com/