


RZ1065SMD

Surface Mounted Light With Die-casting Aluminum Led 10W 700lm CRI80 Diffused 220VAC 80*120*H245mm 50.000h IP65



Description

Housing and wall fixture: Die-casting Aluminum, Pre-treated before powder coating ensuring high corrosion resistance, No-Rinse surface treatment. Optimised surface for reduced accumulation of dirt, with a high level of weather resistance. Durable silicone rubber gasket. Tamper-proof screw. Plastic cover.

Surface mounting box for easy wiring or conduit connection when wiring from behind is not possible.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP65: dust-proof and water jet-proof.



Technical data

Light source	LED SMD
System Wattage	10W
Luminous flux	700lm
Number of led lamp	-
Luminous efficiency	70lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>80, [CRI>90]
Colour Deviation	SDCM<3
Beam Angle	Diffused
Rotation Angle	-
Anti-glare Rating	-
Service Lifetime	50.000 Hrs L80 B20 Ta35
Ingress Protection	IP65
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-30°C ~ 50°C
Frame	Aluminum
Finishing	Matt White, Matt Black or Option
Lighting control (option)	Dali, 0-10V, Triac, Wireless

Accessories

-

Notes

-

