

Model	Dimension	Cut-out
RZ1095DLA	D105*H38mm	D95mm
RZ15125DLA	D140*H38mm	D125mm
RZ20160DLA	D180*H45mm	D140mm
RZ25160DLA	D180*H45mm	D140mm

RZ1095DLA

Recessed Downlight Led 10W 1100lm CRI80 90° D105 50.000h White IP44

RZ15125DLA

Recessed Downlight Led 15W 1650lm CRI80 90° D140 50.000h White IP44

RZ20160DLA

Recessed Downlight Led 20W 2200lm CRI80 90° D180 50.000h White IP44

RZ25160DLA


Recessed Downlight Led 25W 2750lm CRI80 90° D180 50.000h White IP44

Description

Housing: Cast aluminium, excellent thermal management can effectively guarantee the LED's long-term stability. The front panel board is high translucent acrylic, which ensures the light even, soft and high transmittance. Instant start, no flickering, no humming, no hazardous material.

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.



Technical data

Light source	LED SMD
System Wattage	10W 15W 20W 25W
Luminous flux	1100lm 1650lm 2200lm 2750lm
Luminous efficiency	110lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>80, [CRI>90]
Colour Deviation	SDCM<3
Beam Angle	90°
Cut-Off Angle	-
Tilt Angle	-
Anti-glare Rating	UGR<19
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP44
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum & PMMA
Finishing	Matt White
Lighting control (option)	Dali, 0-10V, Triac, Wireless

Accessories

-

Notes

-

