



### RZ125AXL

Recessed Adjustable Downlight With Anti-Glare Reflector D140

### RZ25MXL

Led Module 25W 2125lm CRI90 50.000h IP44

### RZ30MXL

Led Module 30W 2550lm CRI90 50.000h IP44

### RZ35MXL

Led Module 35W 2975lm CRI90 50.000h IP44

### Description

Housing: Cast aluminium, Adjustable, designed as heat sink, with connection cable. 0°-25° tilt, 360° rotation. Fixing ring: Matt White, Matt Black, Customized.

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Anti-glare cone with covered mounting detail: Polymethyl, Chrome, Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light. Optical cut-off 38°. Deep anti-glare design, protect the eye.

Protection Class III.



### Technical data

|                           |   |
|---------------------------|---|
| Light source              | MODULE LED COB                              |
| System Wattage            | 25W   30W   35W                             |
| Luminous flux             | 2125lm   2550lm   2975lm                    |
| Luminous efficiency       | 85lm/w or option                            |
| Colour Temperature        | 2700K, 3000K, 4000K, 6000K, [2700~6000K]    |
| Colour Rendering Index    | CRI>90                                      |
| Colour Deviation          | SDCM<3                                      |
| Beam Angle                | 15°, 24°, 36°, 60°                          |
| Cut-Off Angle             | 38°   |
| Rotation Angle            | 25° Tilt   360° Swivel                      |
| Anti-glare Rating         | UGR<16                                      |
| Service Lifetime          | 50.000 Hrs L80 B20 Ta25                     |
| Ingress Protection        | IP44  |
| Operation Voltage         | 220-240VAC, 50Hz                            |
| Operation Temperature     | -20°C ~ 45°C                                |
| Frame                     | Aluminum                                    |
| Finishing                 | Matt White, Matt Black                      |
| Lighting control (option) | Dali, 0-10V, Triac, Wireless, Tunable White |

### Accessories

Honeycomb can be optionally sold separately

### Notes

-

