




RZ24BLA

Bollard Light With Die-casting Aluminum, PMMA Transparent Diffuser Cover Led 24W 1560lm CRI80 220VAC D185mm 50.000h IP65



RZ12BLA

Bollard Light With Die-casting Aluminum, PMMA Transparent Diffuser Cover Led 12W 780lm CRI80 220VAC D120mm 50.000h IP65

Description

Garden bollard light designed to use LED lamps and a spot optic. Consists of an optical assembly and a base.

Housing, Upper cover and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.

Luminaire head with PMMA Transparent Diffuser Cover, 360° light guidance ring.

Anti-glare cone: corrosion-resistant cast aluminum. Glare-free above the light aperture.

Mounting accessories to be ordered separately.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: high-power LEDs on metal-core PCB.

Protection mode IP65: dust-proof and water jet-proof.



Technical data

Light source	LED SMD	
System Wattage	24W	12W
Luminous flux	1560lm	780lm
Number of led lamp	-	
Luminous efficiency	65lm/w or option	
Colour Temperature	2700K, 3000K, 4000K, 6000K	
Colour Rendering Index	CRI>80, [CRI>90]	
Colour Deviation	SDCM<3	
Beam Angle	Diffused	
Rotation Angle	-	
Anti-glare Rating	UGR<19	
Service Lifetime	50.000 Hrs L70 B30 Ta35	
Ingress Protection	IP65	
Operation Voltage	220-240VAC, 50Hz	
Operation Temperature	-30°C ~ 50°C	
Frame	Aluminum	
Finishing	Matt Black or Option	
Lighting control (option)	Dali, 0-10V, Triac, Wireless	

Accessories

-

Notes

-