



Indoor | Led Strip

RZ1520CST

CCT Tunable Led Strip 15W/m 1500lm [27K 710lm 60K 790lm] CRI90 2700K~6000K 24VDC 50.000h IP20 5M/roll





RZ1565CST

CCT Tunable Led Strip 15W/m 1500lm [27K 710lm 60K 790lm] CRI90 2700K~6000K 24VDC 50.000h IP65 5M/roll









Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, 3M tape available. High-energy efficacy achieving up to 100lm/W, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area.

No need to attach aluminum profile for heat sink, various of connection accessories can be optionally sold separately.

Customized length available up to 5m per roll.

Change atmosphere by tuning the color temperature by Tunable White (2700K \sim 6000K) and dimming control systems are for choice.

Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting usages.

Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.



















Technical data

Light source LED SMD System Wattage 15W/m

Luminous flux 1500lm [27K 710lm 60K 790lm]

Luminous efficiency 100lm/w or option

Colour Temperature 2700K ~ 6000K Adjustable

Colour Rendering Index CRI>90 [CRI95]

Colour Deviation SDCM<3
Beam Angle 120°
Max.Length 5m
Cut length 100mm

Led/m 120pcs
Anti-glare Rating -

Service Lifetime 50.000 Hrs L70 B20 Ta25

Ingress Protection IP20 | IP65 | Option

Operation Voltage 24VDC Operation Temperature $-20^{\circ}\text{C} \sim 45^{\circ}\text{C}$

Lighting control (option) Dali, 0-10V, Triac, Wireless, Tunable White

Accessories









RZ-ST03A RZ-S

RZ-ST03B

RZ-ST0365A

RZ-ST0365B

Notes

_