



RZ1520RSP


RGB Pixel Led Strip 15W/m RGB [R 130lm G 314lm B 76lm] 24VDC 50.000h IP20 5M/roll

RZ1567RSP

RGB Pixel Led Strip 15W/m RGB [R 130lm G 314lm B 76lm] 24VDC 50.000h IP67 5M/roll


Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, tape available. High-energy efficacy achieving, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area. Customized length available up to 5~20m per roll. Auto address-edit, auto addressing, self-adaption Reset function, no need to edit address for maintenance Compatible to DMX512 (1990) signal protocol Adopt parallel differential signal transmitted, support addressing Max 4096 channels Big loading quantilies, strong anti-interference, long distance for transmittance Self-checking function for open-circuit of IC Over-temperature protection. Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting usages. Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.



Technical data

Light source	LED SMD
System Wattage	15W/m [3x5W]
Luminous flux	[R 130lm G 314lm B 76lm]
Luminous efficiency	-
Colour Temperature	RGB
Colour Rendering Index	-
Colour Deviation	SDCM<3
Beam Angle	120°
Max.Length	5m [optional]
Cut length	100mm
Led/m	70pcs
Pixel	10pix/m
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP20 IP67 Option
Operation Voltage	24VDC
Operation Temperature	-20°C ~ 45°C
Lighting control (option)	DMX512, Dali, 0-10V, Wireless



Accessories



Notes

-