



Indoor | Led Strip

RZ1520RST

RGB Led Strip 15W/m RGB [R 155lm G 300lm B 90lm] 24VDC 50.000h IP20 5M/roll



RZ1565RST

RGB Led Strip 15W/m RGB [R 155lm G 300lm B 90lm] 24VDC 50.000h IP65 5M/roll





Description

LED Strip, adopting self-encapsulated LED, highlight SMD, flexible FPC, 3M tape available. High-energy efficacy achieving up to 100lm/W, 3 steps MacAdam, soft light to perfectly present the object without black spot and dark area.

No need to attach aluminum profile for heat sink, various of connection accessories can be optionally sold separately.

Customized length available up to 5m per roll.

Change atmosphere by tuning the color temperature RGB, R (Red), G (Green), B (Blue), Customized and dimming control systems are for choice.

Short cuttable unit suitable for furniture lighting, and for unpredictable requirements on site, applying to indoor and outdoor lighting, furniture, advertisement and other supporting

Protections grades of IP55, IP65, IP66, IP67 and IP68 can be achieved by adopting silicone integrated extrusion, nano coating and other protection processes.
























1.0=43.670mW/nm

pectrum

1. 0

0.6

0. 4

0. 2

0.0

Technical data

Light source LED SMD System Wattage 15W/m [3x5W] [R 155lm G 300lm B 90lm] Luminous flux

Luminous efficiency RGB, Red, Green, Blue, Option Colour Temperature

Colour Rendering Index SDCM<3 Colour Deviation Beam Angle 120° Max.Length 5m Cut length 100mm Led/m 60pcs

Service Lifetime 50.000 Hrs L70 B20 Ta25

Ingress Protection IP20 IP65 Option

Operation Voltage 24VDC Operation Temperature -20°C ~ 45°C

Lighting control (option) DMX512, Dali, 0-10V, Wireless



580 Wavelength(nm)

Accessories

Anti-glare Rating









RZ-ST04A

RZ-ST04B

RZ-ST0465A

RZ-ST0465B

Notes