



RZ1562DFR


Fixed Black Ring Downlight Led 15W 1125lm CRI90 D70 IP54



10W

spot 15°			medium 24°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	4049	ø0.30	1	3505	ø0.39
2	1012	ø0.61	2	876.2	ø0.79
3	449.9	ø0.92	3	389.4	ø1.19
4	253.1	ø1.23	4	291.0	ø1.58
5	162.0	ø1.54	5	140.2	ø1.98

wide 36°		
h(m)	E(lx)	ø(m)
1	1619	ø0.64
2	404.8	ø1.29
3	179.9	ø1.94
4	101.2	ø2.59
5	64.77	ø3.24



62mm
5-25mm

Description

Housing: cast aluminium, designed as heat sink, with connection cable. Fixing ring: polymer, Baffle color: Black, White, Custom.

Mounting ring: White. Expanding clamp fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: high-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Features: Low UGR; Glareless; Sharp beam; Narrow beam; High lux intensity; High CRI, ... Anti-glare cone with covered mounting detail: polymer, white or Black. Optical cut-off 40°.

The luminaire is protected on the room side against splashing water.

Protection Class III.



Technical data

Light source	LED COB
System Wattage	15W – 350mA
Luminous flux	1125lm
Luminous efficiency	75lm/w
Colour Temperature	2700K, 3000K, 4000K
Colour Rendering Index	CRI90
Colour Deviation	SDCM<3
Beam Angle	15°, 24°, 36°
Cut-Off Angle	40°
Tilt Angle	-
Anti-glare Rating	UGR<16
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP54
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum
Finishing	Matt White, Matt Black
Lighting control (option)	Dali, 0-10V, Triac, Wireless

Accessories

-

Notes