



Model	Dimension	Model	Dimension
RZ10SMT	D55*L115mm	RZ30SMT	D70*L155mm
RZ15SMT	D55*L115mm	RZ35SMT	D85*L155mm
RZ20SMT	D70*L135mm	RZ40SMT	D85*L155mm

### RZ10SMT

Surface Mounted Adjustable Spotlight Led 10W 850lm CRI90 D55\*L115 50.000h IP20

### RZ15SMT

Surface Mounted Adjustable Spotlight Led 15W 1275lm CRI90 D55\*L115 50.000h IP20

### RZ20SMT

Surface Mounted Adjustable Spotlight Led 20W 1700lm CRI90 D70\*L135 50.000h IP20

### RZ30SMT

Surface Mounted Adjustable Spotlight Led 30W 2550lm CRI90 D70\*L155 50.000h IP20

### RZ35SMT

Surface Mounted Adjustable Spotlight Led 35W 2975lm CRI90 D85\*L155 50.000h IP20

### RZ40SMT

Surface Mounted Adjustable Spotlight Led 40W 3400lm CRI90 D85\*L155 50.000h IP20

### Description

Housing: cast aluminium, powder-coated; 355° rotation, 90° tilt on the bracket. Color: Matt Black, Matt White, Customized.

Bracket: cast aluminium/polymer, coated; 2-pin connection.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Baffle color: Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light.



### Technical data

Light source	LED COB
System Wattage	10W   15W   20W   30W   35W   40W
Luminous flux	850lm   1275lm   1700lm   2550lm   2975lm   3400lm
Luminous efficiency	85lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>90
Colour Deviation	SDCM<3
Beam Angle	15°, 30°, 45°
Cut-Off Angle	-
Tilt Angle	90° Tilt   330° Swivel
Anti-glare Rating	UGR<19
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP20
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum
Finishing	Matt White, Matt Black
Lighting control (option)	Dali, 0-10V, Triac, Wireless

### Accessories

-

### Notes

-

