



Model	Dimension	Model	Dimension
RZ10TR	D55*L115mm	RZ30TR	D70*L155mm
RZ15TR	D55*L115mm	RZ35TR	D85*L155mm
RZ20TR	D70*L135mm	RZ40TR	D85*L155mm

RZ10TR

Track Light Led 10W 850lm CRI90 D55*L115 50.000h IP20

RZ15TR

Track Light Led 15W 1275lm CRI90 D55*L115 50.000h IP20

RZ20TR

Track Light Led 20W 1700lm CRI90 D70*L135 50.000h IP20

RZ30TR

Track Light Led 30W 2550lm CRI90 D70*L155 50.000h IP20

RZ35TR

Track Light Led 35W 2975lm CRI90 D85*L155 50.000h IP20

RZ40TR

Track Light Led 40W 3400lm CRI90 D85*L155 50.000h IP20

Description

Housing: Cast aluminium, powder-coated; 355° rotation, 90° tilt on the bracket. Color: Matt Black, Matt White, Customized.

Bracket: cast aluminium/polymer, coated; 2-pin connection.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Baffle color: Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light.



Technical data

Light source	LED COB
System Wattage	10W 15W 20W 30W 35W 40W
Luminous flux	850lm 1275lm 1700lm 2550lm 2975lm 3400lm
Luminous efficiency	85lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K
Colour Rendering Index	CRI>90
Colour Deviation	SDCM<3
Beam Angle	15°, 30°, 45°
Cut-Off Angle	-
Tilt Angle	90° Tilt 330° Swivel
Anti-glare Rating	UGR<19
Service Lifetime	50.000 Hrs L70 B20 Ta25
Ingress Protection	IP20
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum
Finishing	Matt White, Matt Black
Lighting control (option)	Dali, 0-10V, Triac, Wireless

Accessories

-

Notes

-

