

RZ1866MLC

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 18W 1440lm CRI80 L1000mm 50.000h IP66




RZ2466MLC

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 24W 1920lm CRI80 L1000mm 50.000h IP66





RZ3666MLC

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 36W 2880lm CRI80 L1000mm 50.000h IP66



Description

LED linear luminaire for wall washer and LED video display application.
 Housing: Die-casting Aluminum, Anti-Corrosion, surface with anodizing treatment and optimised for reduced accumulation of dirt, with a high level of weather resistance. Two mounting brackets for positioning as required: corrosion-resistant aluminium. 135° tilt.
 Luminaire head with transparent toughened non-reflective glass, resist the impact and friction, has excellent rainwater clean ability.
 Control gear: 2 cable entries. Through-wiring possible. [2-5] 3-pole terminal block.
 LED module: High-power LEDs on metal-core PCB. Lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.
 Constant current driver with PWM gray control installed inside, RGB gray level can reach to 65 degree equally, make the dynamic light-dimmer more soft, and the color richer.
 DMX512 and Dimming driver can be optionally sold separately, Powerful interface adopts high reliable bus connect, all has the function of automatic addressing.
 Protection mode IP66: dust-proof and water jet-proof.



Technical data

Light source	LED COB		
System Wattage	18W	24W	36W
Luminous flux	1440lm	1920lm	2880lm
Number of led lamp	18 Led	24 Led	36 Led
Luminous efficiency	80lm/w or option		
Colour Temperature	2700K, 3000K, 4000K, 6000K, [RGB]		
Colour Rendering Index	CRI>80, [CRI>90]		
Colour Deviation	SDCM<3		
Beam Angle	8°, 15°, 20°, 30°, 60°, 15x30°, 10x60°		
Rotation Angle	135° tilt		
Anti-glare Rating	Accessory options		
Service Lifetime	50.000 Hrs L80 B20 Ta35		
Ingress Protection	IP66		
Operation Voltage	100-240VAC, 50Hz		24VDC
Operation Temperature	-30°C ~ 50°C		
Frame	Aluminum		
Finishing	Sliver, Grey, Matt White, Matt Black or Option		
Lighting control (option)	Dali, 0-10V, Triac, Wireless, DMX512		

Accessories

Honeycomb and Anti-glare shield can be optionally sold separately

Notes

-