


RZ18XRD

Double Round Recessed Adjustable Downlight Led 2*9W 1600lm CRI90 D105mm 50.000h IP44



RZ24XRD

Double Round Recessed Adjustable Downlight Led 2*12W 1920lm CRI90 D105mm 50.000h IP44

Description

Designed for shallow ceiling void. With the modularized system, it's easy to use and easy to maintain.

Housing: cast aluminium, powder-coated, connection cable. Ceiling fixture: metal. Includes control gear with Led driver. 2-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Anti-glare cone with covered mounting detail: Polymethyl, Chrome, Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light. Cut-off angle 30° with Anti-glare Rating UGR<19.



Technical data

Light source	LED COB	
System Wattage	2*9W	2*12W
Luminous flux	2*800lm	2*960lm
Luminous efficiency	85lm/w or option	
Colour Temperature	2700K, 3000K, 4000K, 6000K	
Colour Rendering Index	CRI>90	
Colour Deviation	SDCM<3	
Beam Angle	15°, 24°, 36°, 60°	
Cut-Off Angle	30°	
Tilt Angle	-	
Anti-glare Rating	UGR<19	
Service Lifetime	50.000 Hrs L70 B20 Ta25	
Ingress Protection	IP44	
Operation Voltage	220-240VAC, 50Hz	
Operation Temperature	-20°C ~ 45°C	
Frame	Aluminum	
Finishing	Matt White, Matt Black	
Lighting control (option)	Dali, 0-10V, Triac, Wireless	

Accessories

-

Notes

-

