






30° 12W/ 15W - H85

156*85

ع 148*75mm



Indoor | Downlight

RZ2775DSDF

Double Square Recessed Adjustable Downlight With Anti-Glare Reflector Led $2^{\star}\,7W$ $2^{\star}595Im$ CRI90 50.000h IP44

RZ2975DSDF

Double Square Recessed Adjustable Downlight With Anti-Glare Reflector Led 2*9W 2*765lm CRI90 50.000h IP44

RZ21275DSDF

Double Square Recessed Adjustable Downlight With Anti-Glare Reflector Led $2^{\star}12W$ $2^{\star}1020Im$ CRI90 50.000h IP44

RZ21575DSDF

Double Square Recessed Adjustable Downlight With Anti-Glare Reflector Led $2^{\star}15W$ $2^{\star}1275Im$ CRI90 50.000h IP44

Description

Housing: Cast aluminium, Adjustable, designed as heat sink, with connection cable. $0^{\circ}-30^{\circ}$ tilt, 355° rotation. Fixing ring: Matt White, Matt Black, Customized.

Mounting ring: Expanding spring fixing for ceiling thicknesses of 5-30mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, DMX, Wireless, Tuya. Anti-glare cone with covered mounting detail: Mirror Silver, Mirror Black, Mirror Gold, Matt Silver, Matt Black, Matt Gold, Customized. High quality optical diffuser reduces LED dazzle light. Optical cut-off angle 45°. Deep anti-glare design, protect the eye.



Technical data

| Light source | LED COB | | | |
|---------------------------|---|--------|--------|--------|
| System Wattage | 2*7W | 2*9W | 2*12W | 2*15W |
| Luminous flux | 1190lm | 1530lm | 2040lm | 2550lm |
| Luminous efficiency | 85lm/w or option | | | |
| Colour Temperature | 2700K, 3000K, 4000K, 6000K, [2700~6500K] | | | |
| Colour Rendering Index | CRI>90; [CRI>95] | | | |
| Colour Deviation | SDCM<3 | | | |
| Beam Angle | 10°, 15°, 24°, 38°, 50° | | | |
| Cut-Off Angle | 45° | | | |
| Rotation Angle | 30° Tilt 355° Swivel | | | |
| Anti-glare Rating | UGR<16; [UGR<13] | | | |
| Service Lifetime | 50.000 Hrs L80 B20 Ta25 | | | |
| Ingress Protection | IP44 | | | |
| Operation Voltage | 220-240VAC, 50Hz | | | |
| Operation Temperature | -20°C ~ 45°C | | | |
| Frame | Aluminum | | | |
| Finishing | Matt White, Matt Black, Customized | | | |
| Reflector | Silver, Black, Gold, Customized | | | |
| Lighting control (option) | Dali, 0-10V, Triac, DMX, Wireless, Tuya App | | | |

Accessories



Notes

RiZO | Lighting & Solution