



RZ30PLA

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 30W 3600lm CRI80 220VAC D200*H3500mm 100.000h IP66 IK08

RZ45PLA

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 45W 5400lm CRI80 220VAC D200*H4000mm 100.000h IP66 IK08

RZ45PLA

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 45W 5400lm CRI80 220VAC D200*H4500mm 100.000h IP66 IK08

Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.
 Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate. Smooth round decorative ambient lighting post top with clear PMMA diffuser. Mounting accessories to be ordered separately.
 Control gear: 1 cable entries. 3-pole terminal block.
 LED module: high-power LEDs on metal-core PCB.
 Protection mode IP66: dust-proof and water jet-proof.
 Maximum wind load resistance is 160km/h.



Technical data

Light source	LED SMD	
System Wattage	30W	45W
Luminous flux	3600lm	5400lm
Number of led lamp	-	
Luminous efficiency	120lm/w or option	
Colour Temperature	3000K, 4000K, 5000K	
Colour Rendering Index	CRI>80	
Colour Deviation	SDCM<5	
Beam Angle	Diffused	
Rotation Angle	-	
Anti-glare Rating	-	
Service Lifetime	100.000 Hrs L70 B30 Ta35	
Ingress Protection	IP66	
Operation Voltage	100-264VAC, 50Hz	
Operation Temperature	-40°C ~ 60°C	
Frame	Aluminum	
Finishing	Matt Black or Option	
Lighting control (option)	Dali, 0-10V, Triac, Wireless	

Accessories

-

Notes

-