



RZ25PLH

Pole Light With Extruded Aluminum Led 25W 2500lm CRI80 220VAC 180*180*H2500mm 100.000h IP66 IK08

RZ30PLH

Pole Light With Extruded Aluminum Led 30W 3000lm CRI80 220VAC 180*180*H3000mm 100.000h IP66 IK08

RZ35PLH

Pole Light With Extruded Aluminum Led 35W 3500lm CRI80 220VAC 180*180*H3500mm 100.000h IP66 IK08

RZ35PLH

Pole Light With Extruded Aluminum Led 35W 3500lm CRI80 220VAC 180*180*H4000mm 100.000h IP66 IK08

Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.
 Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.
 Luminaire head with diffused light guidance ring.
 Mounting accessories to be ordered separately.
 Control gear: 1 cable entries. 3-pole terminal block.
 LED module: high-power LEDs on metal-core PCB.
 Protection mode IP66: dust-proof and water jet-proof.
 Maximum wind load resistance is 160km/h.



Technical data

Light source	LED COB				
System Wattage	25W		30W		35W
Luminous flux	2500lm		3000lm		3500lm
Number of led lamp	1 Led				
Luminous efficiency	100lm/w or option				
Colour Temperature	3000K, 4000K, 5000K				
Colour Rendering Index	CRI>80				
Colour Deviation	SDCM<5				
Beam Angle	Diffused				
Rotation Angle	-				
Anti-glare Rating	-				
Service Lifetime	100.000 Hrs L70 B30 Ta35				
Ingress Protection	IP66				
Operation Voltage	100-264VAC, 50Hz				
Operation Temperature	-40°C ~ 60°C				
Frame	Aluminum				
Finishing	Matt Black or Option				
Lighting control (option)	Dali, 0-10V, Triac, Wireless				

Accessories

-

Notes

-