



### RZ3666MLD

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 36W 2880lm CRI80 L500mm 50.000h IP66

### RZ5466MLD

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 54W 4320lm CRI80 L500mm 50.000h IP66

### RZ7266MLD

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 72W 5760lm CRI80 L1000mm 50.000h IP66

### RZ10866MLD

Surface Mounted Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 108W 8640lm CRI80 L1000mm 50.000h IP66

### Description

LED linear luminaire for wall washer and LED video display application.  
 Housing: Die-casting Aluminum, Anti-Corrosion, surface with anodizing treatment and optimised for reduced accumulation of dirt, with a high level of weather resistance. Two mounting brackets for positioning as required: corrosion-resistant aluminium. 135° tilt.  
 Luminaire head with transparent toughened non-reflective glass, resist the impact and friction, has excellent rainwater clean ability.  
 Control gear: 2 cable entries. Through-wiring possible. [2-5] 3-pole terminal block.  
 LED module: High-power LEDs on metal-core PCB. Lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.  
 Constant current driver with PWM gray control installed inside, RGB gray level can reach to 65 degree equally, make the dynamic light-dimmer more soft, and the color richer.  
 DMX512 and Dimming driver can be optionally sold separately, Powerful interface adopts high reliable bus connect, all has the function of automatic addressing.  
 Protection mode IP66: dust-proof and water jet-proof.



### Technical data

Light source	LED COB			
System Wattage	36W	54W	72W	108W
Luminous flux	2880lm	4320lm	5760lm	8640lm
Number of led lamp	27 Led	27 Led	54 Led	54 Led
Luminous efficiency	80lm/w or option			
Colour Temperature	2700K, 3000K, 4000K, 6000K, [RGB]			
Colour Rendering Index	CRI>80, [CRI>90]			
Colour Deviation	SDCM<3			
Beam Angle	5°, 8°, 15°, 20°, 30°, 60°, 15x30°, 10x60°			
Rotation Angle	135° tilt			
Anti-glare Rating	Accessory options			
Service Lifetime	50.000 Hrs L80 B20 Ta35			
Ingress Protection	IP66			
Operation Voltage	100-240VAC, 50Hz			24VDC
Operation Temperature	-30°C ~ 50°C			
Frame	Aluminum			
Finishing	Sliver, Grey, Matt White, Matt Black or Option			
Lighting control (option)	Dali, 0-10V, Triac, Wireless, DMX512			

### Accessories

Honeycomb and Anti-glare shield can be optionally sold separately

### Notes

-