



### RZ30PLB

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 30W 3600lm CRI80 220VAC D208\*H4000mm 100.000h IP66 IK08

### RZ40PLB

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 40W 4800lm CRI80 220VAC D208\*H4000mm 100.000h IP66 IK08

### RZ55PLB

Pole Light With Die-cast Aluminum housing, PMMA Transparent Diffuser Cover and Aluminum Poles Led 55W 6600lm CRI80 220VAC D208\*H4000mm 100.000h IP66 IK08

### Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.

Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.

Smooth round decorative ambient lighting post top with clear PMMA diffuser.

Mounting accessories to be ordered separately.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: high-power LEDs on metal-core PCB.

Protection mode IP66: dust-proof and water jet-proof.

Maximum wind load resistance is 160km/h.



### Technical data

Light source	LED SMD		
System Wattage	30W	40W	55W
Luminous flux	3600lm	4800lm	6600lm
Number of led lamp	-		
Luminous efficiency	120lm/w or option		
Colour Temperature	3000K, 4000K, 5000K		
Colour Rendering Index	CRI>80		
Colour Deviation	SDCM<5		
Beam Angle	Diffused		
Rotation Angle	-		
Anti-glare Rating	-		
Service Lifetime	100.000 Hrs L70 B30 Ta35		
Ingress Protection	IP66		
Operation Voltage	100-264VAC, 50Hz		
Operation Temperature	-40°C ~ 60°C		
Frame	Aluminum		
Finishing	Matt Black or Option		
Lighting control (option)	Dali, 0-10V, Triac, Wireless		

### Accessories

-

### Notes

-