



RZ20UGA

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 20W 2400lm CRI80 220VAC D208*H550mm 100.000h IP66 IK08

RZ30UGA

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 30W 3600lm CRI80 220VAC D208*H550mm 100.000h IP66 IK08

RZ40UGA

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 40W 4800lm CRI80 220VAC D208*H550mm 100.000h IP66 IK08

RZ55UGA

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 55W 6600lm CRI80 220VAC D208*H550mm 100.000h IP66 IK08

Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.

Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.

Smooth round decorative ambient lighting post top with clear PMMA diffuser.

Pole and Mounting accessories to be ordered separately.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: high-power LEDs on metal-core PCB.

Protection mode IP66: dust-proof and water jet-proof.

Maximum wind load resistance is 160km/h.



Technical data

Light source	LED SMD			
System Wattage	20W	30W	40W	55W
Luminous flux	2400lm	3600lm	4800lm	6600lm
Number of led lamp	-			
Luminous efficiency	120lm/w or option			
Colour Temperature	3000K, 4000K, 5000K			
Colour Rendering Index	CRI>80			
Colour Deviation	SDCM<5			
Beam Angle	Diffused			
Rotation Angle	-			
Anti-glare Rating	-			
Service Lifetime	100.000 Hrs L70 B30 Ta35			
Ingress Protection	IP66			
Operation Voltage	100-264VAC, 50Hz			
Operation Temperature	-40°C ~ 60°C			
Frame	Aluminum			
Finishing	Matt Black or Option			
Lighting control (option)	Dali, 0-10V, Triac, Wireless			

Accessories

-

Notes

-