



RZ4267IGB

Inground Light Stainless Steel 316 Cover, Anti-Corrosion, Transparent Toughened Glass Led 42W 3360lm CRI80 24VDC D330mm 80.000h IP67 With Recessed Box

RZ6067IGB

Inground Light Stainless Steel 316 Cover, Anti-Corrosion, Transparent Toughened Glass Led 60W 4800lm CRI80 24VDC D330mm 80.000h IP67 With Recessed Box

Description

Recessed luminaire that can be installed in concrete floors or in the ground. It is designed to use LED lamps, for lighting, Adjustable optic.

Housing: Die-casting Aluminum with Stainless Steel 316 Cover, Anti-Corrosion, No-Rinse surface treatment. Surface with electrostatic plastic coating and Optimised for reduced accumulation of dirt, with a high level of weather resistance. Stainless steel fasteners in grade 316, Durable silicone rubber gasket.

Luminaire head with transparent toughened non-reflective glass, resist the impact and friction.

Control gear: Longitudinally watertight cable, 1 cable entries. [3] 2-pole terminal block. Installation with separate connection sleeve.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP67: dust-proof and accidental immersion up to 1m deep.

Suitable for walk-over with a maximum static load resistance of 300kg.



Technical data

Light source	LED COB
System Wattage	42W 60W
Luminous flux	3360lm 4800lm
Number of led lamp	12 Led
Luminous efficiency	80lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K, [RGB]
Colour Rendering Index	CRI>80, [CRI>90]
Colour Deviation	SDCM<3
Beam Angle	8°, 15°, 20°, 30°, 45°, 60°, [15°x30°], [10°x70°]
Rotation Angle	15° Tilt
Anti-glare Rating	-
Service Lifetime	80.000 Hrs L80 B20 Ta35
Ingress Protection	IP67
Operation Voltage	100-240VAC, 50Hz 24VDC
Operation Temperature	-30°C ~ 50°C
Frame	Aluminum & Stainless Steel 316 Cover
Finishing	Non-Color
Lighting control (option)	Dali, 0-10V, Triac, Wireless, DMX512

Accessories

Recessed box

Notes

-