



### RZ1167ILB

Inground Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 11W 880lm CRI80 24VDC L500mm 50.000h IP67

### RZ2167ILB

Inground Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 21W 1680lm CRI80 24VDC L1000mm 50.000h IP67

### RZ2867ILB

Inground Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 28W 2240lm CRI80 24VDC L1000mm 50.000h IP67

### RZ4267ILB

Inground Linear Light With Die-casting Aluminum, Transparent Toughened Glass Cover Led 42W 3360lm CRI80 24VDC L1000mm 50.000h IP67

### Description

LED linear luminaire for inground, ceiling-recessed and LED video display application. Housing: Die-casting Aluminum, Anti-Corrosion, surface with anodizing treatment and optimised for reduced accumulation of dirt, with a high level of weather resistance. Two mounting brackets for positioning as required: corrosion-resistant aluminium. 135° tilt. Luminaire head with transparent toughened non-reflective glass, resist the impact and friction, has excellent rainwater clean ability. Control gear: 2 cable entries. Through-wiring possible. [2-5] 2-pole terminal block. LED module: High-power LEDs on metal-core PCB. Lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area. Constant current driver with PWM gray control installed inside, RGB gray level can reach to 65 degree equally, make the dynamic light-dimmer more soft, and the color richer. DMX512 and Dimming driver can be optionally sold separately, Powerful interface adopts high reliable bus connect, all has the function of automatic addressing. Protection mode IP67: dust-proof and accidental immersion up to 1m deep



### Technical data

Light source	LED COB			
System Wattage	11W	21W	28W	42W
Luminous flux	880lm	1680lm	2240lm	3360lm
Number of led lamp	9 Led	18 Led	24 Led	36 Led
Luminous efficiency	80lm/w or option			
Colour Temperature	2700K, 3000K, 4000K, 6000K, [RGB]			
Colour Rendering Index	CRI>80, [CRI>90]			
Colour Deviation	SDCM<3			
Beam Angle	8°, 15°, 20°, 30°, 45°, 60°, 15x30°, 10x60°			
Rotation Angle	10° tilt			
Anti-glare Rating	Accessory options			
Service Lifetime	50.000 Hrs L80 B20 Ta35			
Ingress Protection	IP67			
Operation Voltage	24VDC			
Operation Temperature	-30°C ~ 50°C			
Frame	Aluminum			
Finishing	Sliver, Grey, Matt White, Matt Black or Option			
Lighting control (option)	Dali, 0-10V, Triac, Wireless, DMX512			

### Accessories

Honeycomb can be optionally sold separately

### Notes

-

