


RZ4066SLC

Floodlight With Die-casting Aluminum, Anti-Corrosion, Transparent Toughened Glass Led 40W 3200lm CRI80 D147mm 50.000h IP66 with Grey Color



RZ5066SLC

Floodlight With Die-casting Aluminum, Anti-Corrosion, Transparent Toughened Glass Led 50W 4000lm CRI80 D147mm 50.000h IP66 with Grey Color



Tree

Pole



Pole-2

Mounting



Description

Outdoor floodlight designed to use LED lamps and a spot optic. Consists of an optical assembly and a base.

Housing, hinge and mounting plate: Die-casting Aluminum, Anti-Corrosion, No-Rinse surface treatment. Surface with fluorine carbon spraying and optimised for reduced accumulation of dirt, with a high level of weather resistance. Hinge with 130° tilt. Mounting plate rotatable through 350°. All external screws used are made of A2 stainless steel. Luminaire head with transparent toughened non-reflective glass, resist the impact and friction.

Control gear: 1 cable entries. [2] 3-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Protection mode IP66: dust-proof and water jet-proof.



Technical data

Light source	LED COB	
System Wattage	40W	50W
Luminous flux	3200lm	4000lm
Number of led lamp	5 Led	15 Led
Luminous efficiency	80lm/w or option	
Colour Temperature	2700K, 3000K, 4000K, 6000K, [RGB]	
Colour Rendering Index	CRI>80, [CRI>90]	
Colour Deviation	SDCM<3	
Beam Angle	6°, 8°, 12°, 20°, 30°, 45°, [5x20°], [10x70°]	
Rotation Angle	130° Tilt 350° Swivel	
Anti-glare Rating	Accessory options	
Service Lifetime	50.000 Hrs L80 B20 Ta35	
Ingress Protection	IP66	
Operation Voltage	100-264VAC, 50Hz	24VDC
Operation Temperature	-30°C ~ 50°C	
Frame	Aluminum	
Finishing	Dark Grey, Matt Black or Option	
Lighting control (option)	Dali, 0-10V, Triac, Wireless, DMX512	

Accessories

Ground Spike & Honeycomb can be optionally sold separately

Notes

-

