



Model	Dimensions
RZ6640P	595*595*10mm
RZ31240P	295*1195*10mm
RZ61260P	595*1195*10mm

RZ6640P

Panel Light Led 40W 4000lm 120° 595*595*10mm 50.000h White

RZ31240P

Panel Light Led 40W 4000lm 120° 295*1195*10mm 50.000h White

RZ61260P

Panel Light Led 60W 6000lm 120° 595*1195*10mm 50.000h White

Description

Housing: cast aluminium, excellent thermal management can effectively guarantee the LED's long-term stability. The front panel board is high translucent acrylic, which ensures the light even, soft and high transmittance. Instant start, no flickering, no humming, no hazardous material.

Includes control gear with Led driver separate. 2-pole terminal block.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

RGBW colorful and wireless remote control, meet various applications.

Long life span, more than 50,000 hours, greatly reduce the cost of light source replacement and maintenance.

Good adaptability, easy installation. Multiple installation methods can be applied: drop-ceiling, hanging, recessed, surface mounted with optional accessory kit sold separately.



Technical data

Light source	LED SMD		
System Wattage	40W [600*600]	40W [300*1200]	60W [600*1200]
Luminous flux	4000lm	4000lm	6000lm
Luminous efficiency	100lm/w or option		
Colour Temperature	2700K, 3000K, 4000K, 6000K, RGBW, [2700~6000K]		
Colour Rendering Index	CRI>80		
Colour Deviation	SDCM<3		
Beam Angle	120°		
Cut-Off Angle	-		
Tilt Angle	-		
Anti-glare Rating	UGR<19		
Service Lifetime	50.000 Hrs L70 B20 Ta25		
Ingress Protection	IP40, [IP65]		
Operation Voltage	220-240VAC, 50Hz		
Operation Temperature	-20°C ~ 45°C		
Frame	Aluminum & PMMA		
Finishing	Matt White		
Lighting control (option)	Dali, 0-10V, Triac, Wireless, CCT Tunable White		

Accessories

-

Notes

-

