

### RZ75STM

Square Recessed Trimless Adjustable Downlight With Anti-Glare Reflector SQ74

### RZ07MM

Led Module 7W 595lm CRI90 50.000h IP44

### RZ09MM

Led Module 9W 765lm CRI90 50.000h IP44

### RZ12MM

Led Module 12W 1020lm CRI90 50.000h IP44

### RZ15MM

Led Module 15W 1275lm CRI90 50.000h IP44

### Description

Housing: Cast aluminium, Trimless, Adjustable, designed as heat sink, with connection cable. 0°-25° tilt. Fixing ring: Matt White, Matt Black, Customized.


Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Anti-glare cone with covered mounting detail: Polymethyl, Chrome, Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light. Optical cut-off 38°. Deep anti-glare design, protect the eye.

Protection Class III.



### Technical data

Light source	MODULE LED COB
System Wattage	7W   9W   12W   15W
Luminous flux	595lm   765lm   1020lm   1275lm
Luminous efficiency	85lm/w or option
Colour Temperature	2700K, 3000K, 4000K, 6000K, [2700~6000K]
Colour Rendering Index	CRI>90
Colour Deviation	SDCM<3
Beam Angle	10°, 15°, 24°, 36°, 60°
Cut-Off Angle	38°
Rotation Angle	25° Tilt   360° Swivel
Anti-glare Rating	UGR<16
Service Lifetime	50.000 Hrs L80 B20 Ta25
Ingress Protection	IP44
Operation Voltage	220-240VAC, 50Hz
Operation Temperature	-20°C ~ 45°C
Frame	Aluminum
Finishing	Matt White, Matt Black
Lighting control (option)	Dali, 0-10V, Triac, Wireless, Tunable White

### Accessories

Honeycomb can be optionally sold separately

### Notes

-