



RZ35UGD

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 35W 4200lm CRI80 100.000h 220VAC D590*688mm IP66 IK08

RZ45UGD

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 45W 5400lm CRI80 100.000h 220VAC D590*688mm IP66 IK08

RZ60UGD

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 60W 7200lm CRI80 100.000h 220VAC D590*688mm IP66 IK08

RZ75UGD

Urban Garden With Die-cast Aluminum housing, Glass Transparent Diffuser Cover Led 75W 9000lm CRI80 100.000h 220VAC D590*688mm IP66 IK08

Description

Urban Pole Light, designed to use monochrome LED lamps. It consists of a body, an optical assembly and a fixing base.

Housing, pole and base plate: Corrosion-resistant Extruded Aluminum. Optimised surface for reduced accumulation of dirt. Double powder-coated. Durable silicone rubber gasket. Base plate for mounting on ground socket, concrete anchor or mounting plate.

Smooth round decorative ambient lighting post top with clear PMMA diffuser.

Pole and Mounting accessories to be ordered separately.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: high-power LEDs on metal-core PCB.

Protection mode IP66: dust-proof and water jet-proof.

Maximum wind load resistance is 160km/h.



Technical data

Light source	LED SMD			
System Wattage	35W	45W	60W	75W
Luminous flux	4200lm	5400lm	7200lm	9000lm
Number of led lamp	-			
Luminous efficiency	120lm/w or option			
Colour Temperature	3000K, 4000K, 5000K			
Colour Rendering Index	CRI>80			
Colour Deviation	SDCM<5			
Beam Angle	Diffused			
Rotation Angle	-			
Anti-glare Rating	-			
Service Lifetime	100.000 Hrs L70 B30 Ta35			
Ingress Protection	IP66			
Operation Voltage	100-264VAC, 50Hz			
Operation Temperature	-40°C ~ 60°C			
Frame	Aluminum			
Finishing	Matt Black or Option			
Lighting control (option)	Dali, 0-10V, Triac, Wireless			

Accessories

-

Notes

-