



D80

72mm

5W/ 7W - H80  
9W/ 12W - H98  
15W - H113

### RZF02MR

Recessed Fixed Downlight With Anti-Glare Reflector D80

### RZ05MR

Led Module 5W 425lm CRI90 50.000h IP44

### RZ07MR

Led Module 7W 595lm CRI90 50.000h IP44

### RZ09MR

Led Module 9W 765lm CRI90 50.000h IP44

### RZ12MR

Led Module 12W 1020lm CRI90 50.000h IP44

### RZ15MR

Led Module 15W 1275lm CRI90 50.000h IP44

### Description

Housing: Cast aluminium, Fixed, designed as heat sink, with connection cable. 360° rotation. Fixing ring: Matt White, Matt Black, ...

Mounting ring: white. Expanding spring fixing for ceiling thicknesses of 5-25mm. Includes control gear with Led driver separate. 2-pole terminal block.

LED module: High-power LEDs on metal-core PCB. Collimating lens made of optical Polymethyl. Tender and soft light to perfectly present the object without black spot and dark area.

Dimming driver can be optionally sold separately: Dali, 0-10V, Triac, Wireless.

Anti-glare cone with covered mounting detail: Polymethyl, Chrome, Matt White, Matt Black, Customized. High quality optical diffuser reduce LED dazzle light. Optical cut-off 40°. Deep anti-glare design, protect the eye.



### Technical data

Light source	MODULE MR16 LED COB				
System Wattage	5W	7W	9W	12W	15W
Luminous flux	425lm	595lm	765lm	1020lm	1275lm
Luminous efficiency	85lm/w or option				
Colour Temperature	2700K, 3000K, 4000K, 6000K, [ 2700~6000K ]				
Colour Rendering Index	CRI>90, [ CRI97 ]				
Colour Deviation	SDCM<3				
Beam Angle	15°, 24°, 38°, [ 10°, 10°x60°, 30°x60° ]				
Cut-Off Angle	40°				
Tilt Angle	-				
Anti-glare Rating	UGR<16				
Service Lifetime	50.000 Hrs L70 B20 Ta25				
Ingress Protection	IP44				
Operation Voltage	220-240VAC, 50Hz				
Operation Temperature	-20°C ~ 45°C				
Frame	Aluminum				
Finishing	Matt White, Matt Black				
Lighting control (option)	Dali, 0-10V, Triac, Wireless, Tunable White				

### Accessories

Honeycomb can be optionally sold separately

### Notes

-