



RZG35WDA

Wall Pillar Light Up & Down With Aluminum 2*GU10 Max.35W 220VAC D60*H210mm IP65

RZG35WSA

Wall Pillar Light Single Fixed With Aluminum GU10 Max.35W 220VAC D60*H135mm IP65

Description

Housing and wall fixture: Die-casting Aluminum, Pre-treated before powder coating ensuring high corrosion resistance, No-Rinse surface treatment. Optimised surface for reduced accumulation of dirt, with a high level of weather resistance. Durable silicone rubber gasket. Tamper-proof screw.

Surface mounting box for easy wiring or conduit connection when wiring from behind is not possible.

Control gear: 1 cable entries. 3-pole terminal block.

LED module: Led GU10. Luminaire head with non-reflective safety glass.

Dimming driver can be optionally sold separately [optional by bulb]: Dali, 0-10V, Wireless.

Protection mode IP65: dust-proof and water jet-proof.



Technical data

Light source	GU10 Max.35W		GU5.3 Max20W
System Wattage	-		
Luminous flux	-		
Number of led lamp	-		
Luminous efficiency	-		
Colour Temperature	-		
Colour Rendering Index	-		
Colour Deviation	-		
Beam Angle	-		
Rotation Angle	-		
Anti-glare Rating	-		
Service Lifetime	-		
Ingress Protection	IP65		
Operation Voltage	220-240VAC, 50Hz		12V
Operation Temperature	-30°C ~ 50°C		
Frame	Aluminum		
Finishing	Matt White, Matt Black or Option		
Lighting control (option)	Dali, 0-10V, Triac, Wireless		

Accessories

-

Notes

-

